PINOUTS GUIDE .COM

Symbol LS2208 barcode handheld scanner interconnection cable pinout
bookmark this page

connector wiring scheme

TOP:

FRONT:

10 pin RJ50 (10P10C)
male connector
at the Scanner

Ads by Google

Rectangular Connectors
IP68 Protection, Lower Cost, More Wiring Space - Heavycon ADVANCE
www.phoenixcontact.com

Pin Number	Pin description for PS2 Kbd use	PIN Description for USB use
1	reserved	jumper to pin 6
2	Power	power
3	Ground	ground
4	Key Clock	reserved
5	Term Data	Data +
6	Key Data	Jump to pin 1
7	Term Clock	Data -
8	reserved	reserved
9	reserved	reserved
10	reserve	reserved

A

B

MINI-B

MINI-A

4 pin USB A or USB B
plug connector
at the PC

This information should be correct, but may be not. **Please, help us to improve this document!**
Is this document CORRECT or INCORRECT? Your opinion will be used to establish document status (showed at the bottom).

Want to add or correct something here? Edit this page!

Pinoutsguide.com > Various peripheral devices pinouts > Pinout of Symbol LS2208 barcode handheld scanner interconnection cable

Is it correct?: unknown

Source(s) of this and additional information: http://www.modul-bio.com/media/Symbol_LS2208_Manual.pdf
Contributor: Andres

no reports

Last updated 2010-06-15 21:49:00. Edit this page.

Is this document correct or incorrect? What is your opinion?

[Discuss at the forum] [Back to index] [SUBMIT new pinout]